

HVA45TD

the smallest VLF test system of its performance class
with integrated Tan Delta Diagnostics

- VLF and DC output
- Sheath Test
- Sheath Fault Location Mode
- Vacuum Bottle Test
- PD system upgrade available
- Insulation Testing

The HVA45TD is a truly compact and portable VLF test set system for testing medium voltage cables. It performs **VLF** and **DC** testing, **sheath testing with sheath fault location mode** and **TD leakage current correction** (guard terminal) is included. Assessments of cable condition can also be carried out by use of **Tan Delta Diagnostics**.

New - the recently introduced **Monitored Withstand Test (MWT)**, a combination of Withstand Testing and Tan Delta Diagnostics in compliance with IEEE 400.2-2013, can be performed.

Performance - the HVA45TD offers outstanding features in terms of size, weight (39 kg) and performance (max. 10 μ F).

Safety - the instrument has two independent earthing devices (electronic and mechanical discharging) and an integrated 12 kV feedback protection system to protect both operator and instrument.

Field use - a watertight and very rugged case with a protection class of IP67 makes additional transport boxes obsolete.

Connectivity - on site, no external PC is needed. All results can be downloaded later by USB or Bluetooth for further investigation and easy report creation on the PC Software.



trolley casing

Features

- Output voltage 45 kV_{peak}, 32 kV_{rms}
- Pure sinusoidal output voltage (load-independent)
- Internal TD measurement with high accuracy (1×10^{-4})
- Tan Delta measurement with various frequencies (0.01 – 0.1 Hz)
- Leakage Guard® - leakage current correction
- Output current 60 mA max.
- 1.0 μ F @ 0.1 Hz @ 32 kV_{rms}
- Highest test capacity of 10 μ F
- Ultra light and compact weight (39 kg)
- Protection class IP67 (with closed lid)
- Total protection – almost unbreakable, watertight, dustproof and corrosion proof case
- Large Colour display (4,3")
- USB and Bluetooth connections
- Cable testing according: IEC60502-2:2015, IEEE400.2-2013, CENELEC HD 620/621, etc.
- Programmable test sequences
- Upgradable with partial discharge diagnostic system (optional)
- Integrated 12 kV transient protection (50 Hz)
- Dual Discharge Device (DDD®), two integrated and automatic discharge devices
- Easily exchangeable HV cable
- Intuitive menu operation
- Sheath Fault Locating (in combination with Earth Fault Locator)¹
- Vacuum Bottle Test
- Insulation Testing

www.b2hv.at

b2
electronicgmbh

¹ not in scope of supply

HVA45TD

the smallest VLF test system of its performance class
with integrated Tan Delta Diagnostics



smallest and lightest
VLF cable test set



trolley casing



unlimited operating
time

Typ	HVA45TD	
Article number	SH0261	
Input voltage	100 - 240 V, 50/60 Hz, 1.200 VA	
Output voltage	VLF sine wave	0 - 45 kV peak, 32 kV rms
	DC	± 0 - 45 kV
	VLF square wave	0 - 45 kV
	accuracy	± 1%
	resolution	0.1 kV
Output current	0 - 60 mA (Resolution 1 µA) Accuracy: ±1%	
Resistance range	0.1 MΩ - 5 GΩ	
Output frequency	0.01 - 0.1 Hz in steps of 0.01 Hz (default 0.1 Hz) - auto frequency	
Tan Delta	Accuracy ± 1 x 10 ⁻⁴	
Output load	1.0 µF @ 0.1 Hz @ 32kV rms 10.0 µF maximum Capacitance! ¹	
Sheath test	max. test voltage	10 kV
	trip current	0.1 mA – 5.0 mA
Sheath fault location ²	max. test voltage	10 kV
	pulse/period	1:3 / 4 s, 1:5 / 4 s, 1:5 / 6 s, 1:9 / 6 s
Output modes	AC (VLF) symmetrical and load-independent across full range, DC (plus or negative polarity), burn-/fault condition or fault trip mode, jacket/sheath testing	
Safety	50 Hz - 12 kV feedback protection/ Dual Discharge Device (internal)	
Record storage	Built-in memory: up to 50 reports & 50 test sequences USB flash drive: unlimited	
Metering	voltage and current (true rms and/or peak), capacitance, resistance, time, flashover voltage	
HV Cable	5 m with clamps	
PC Software	"b2 Control Center" (included)	
Computer interfaces	Bluetooth and USB	
Dimensions LxBxH	500 x 305 x 457 mm (Peli Case)	
Weight	39 kg	
Environment	temperature: storage -25°C to + 70°C, operating -20°C to + 55°C humidity: 5-70 % non condensing	

¹ at lower frequency and voltage | ² in combination with locating device (not in scope of supply)

DHV1365 Rev03 - ENGLISH - Subject to alternations. Errors excepted. Illustrations are not binding.



Riedstrasse 1 | A-6833 Klaus
+43 (0) 5523 57373 | info@b2hv.at

Options

- Partial Discharge Diagnostics System

Scope of delivery

- HVA45TD Testing Device incl. Tan Delta
- PC Software - b2 ControlCenter
- 5 m HV cable
- Power and earthing cable
- Accessory Bag
- USB Stick
- Operating Manual