

HVA60

VLF High Voltage Test Set

- VLF pure sinusoidal voltage
- VLF rectangular voltage
- DC voltage
- Sheath Test
- Sheath Fault Location Mode
- Vacuum Bottle Test

The **HVA60** AC hipot by b2hv is a portable 0.1 Hz VLF cable test system for the testing of medium voltage cables.

Dry system - The HVA60 test set is a dry type test system - have no oil filled components. This means less maintenance, compact and lightweight design and no limitation of operating time.

Safety - The instrument has two independent earthing devices (electronic and mechanical discharging) and a 12 kV feedback protection system to protect both operator and instrument.

Connectivity - On site, no external PC is needed. All results can be downloaded later by USB for further investigation and easy report creation on the PC software.

Solid HV connectors - Robust HV-connectors allow the use of different HV test lead lengths, the quick exchange for a replacement cable, or the simpler upgrade path for connection of diagnostic systems.



Features

- Output voltage 44 kV_{rms}, 62 kV_{peak}
- Pure sinusoidal output voltage (load-independent)
- Output current 40 mA max.
- Highest test capacity of 10 μ F
- Unlimited and continuous duty circle
- Cable testing according: CENELEC HD 620/621, IEEE 400.2-2004, IEC60502-2:2014
- Programmable test sequences
- Upgradable with Partial Discharge diagnostic and Tan Delta system (optional)
- 12kV transient protection (50 Hz)
- Dual Discharge Device (DDD®), two integrated and automatic discharge devices
- Easily exchangeable HV cable
- Vacuum Bottle Test
- Sheath Fault Locating (in combination with Earth Fault Locator) (not included)
- Real time oscilloscope display of output voltage
- Breakdown voltage and load detection (R and C)
- RMS digital metering of voltage and current
- PC software "b2 Control Center" with various reporting functions included

www.b2hv.at

b2
electronicgmbh

HVA60

VLF High Voltage Test Set



smallest and lightest
VLF cable test set



dry system



unlimited operating
time



Transportbox (optional)

HVA60		
Article number	SH0203	
Input Voltage	100 – 240 V, 50/60 Hz, 1.5 kVA	
Output Voltage	Sinusoidal	0 - 62 kV peak, 44 kV rms
	DC	± 0 – 60 kV
	Squarewave	0 - 60 kV
	Accuracy	± 1%
	Resolution	0.1 kV
Output Current	0 – 40 mA (Resolution 1 µA) Accuracy: ±1%	
Resistance Range	0.1 MΩ...5 GΩ	
Output Frequency	0.01 ... 0.1 Hz in steps of 0.01 Hz (default 0.1 Hz) - auto frequency	
Output Load	1.0 µF @ 0.1 Hz @ 44 kV rms 2.0 µF @ 0.05 Hz @ 44 kV rms 5.0 µF @ 0.02 Hz @ 44 kV rms 10.0 µF maximum Capacitance! ¹	
Sheath Test	Unmax	10 kV
	Trip Current	0.1 mA – 5.0 mA
Sheath Fault Location ²	Unmax	10 kV
	Pulse/Period	1:3 / 4 s, 1:5 / 4 s, 1:5 / 6 s, 1:9 / 6 s
Output Modes	AC (VLF) Symmetrical and load independent across full range, DC (plus or negative polarity), Burn-/Fault Condition or Fault Trip Mode, Jacket / Sheath Testing	
Safety	50 Hz 12 kV Feedback Protection / Dual Discharge Device (internal)	
Memory	50 Test Record Stored USB almost unlimited	
Metering	Voltage and Current (True rms and / or peak), Capacitance, Resistance, Time, Flashover Voltage	
HV-Cable	5 m with MC contact and alligator clamps	
Software	"b2 Control Center" (included)	
Computer interfaces	RS232	standard
	USB	Flash Drive
Dimensions	L 450 x W 340 x H 520 mm	
Weight	57 kg	
Environmental conditions	Storage: -25°C to + 70°C Operating: -10°C to + 50°C Humidity: 5-85% non condensing	

¹ at lower frequency and voltage | ² in combination with locating device (not in scope of supply)

DHV1210 Rev04 - ENGLISH - Subject to alternations. Errors excepted. Illustrations are not binding.



Riedstrasse 1 | A-6833 Klaus
+43 (0) 5523 57373 | info@b2hv.at

Options

- External Tan Delta Diagnostics System TD60 / TD60-MC
- Partial Discharge with integrated Tan Delta Diagnostics System PDTD60-2

Scope of delivery

- HVA60 Testing Device
- PC Software - b2 ControlCenter
- HV cable 5 m
- Power and earthing cable
- USB Stick
- Operating Manual